



The Strategic Role of


Off-Grid Renewable Gases



elogicación established lo ajpartition el












7% of off grid homes heat with coal3 and a further 23% with fuel oil3. These fuels have high air pollution and greenhouse gas emissions.

Old Buildings are Common and Less Energy Efficient



Building Stock Diversity and Prominence of Hard-to-Treat Buildings

There is a broad variety of building types and ages in the EU. Generally, older buildings are less energy efficient, as shown on the bar chart above⁵, these hard-to-treat buildings are common in rural areas and require more

There is a broad mix of heating technologies in the EU, heating oil and coal are widely used for dwellings not connected to the gas grid3. These fuels have high carbon and air pollution emissions.

Different buildings and consumers require different energy solutions suited to their needs and circumstances, as there is no 'one size fits all' solution. Consumers should be provided with a choice to ensure rapid decarbonisation and a just energy transition.


¹Eurostat (2022) Number of households by degree of urbanisation
²Eurostat (2019) Share of fuels in the final energy consumption in the residential sector for space heating
³FRAUNHOFER ISI (2021) Space heating market summary 2017
⁴ECOFYS (2018) Rural energy in Europe
⁵European Commission (2020) EU Buildings Database




Energy Security and Flexibility

Heating demand varies significantly throughout the year with much higher winter consumption than in summer, as shown on the graph for Germany below⁸. Increasing electrification and penetration of intermittent renewable energy significantly increases the difficulty of operating a reliable electricity grid and managing supply and demand, particularly in off-grid areas which generally have the worst reliability⁷. The graph below shows renewable electricity generation dropping in winter^{8,9} as heat demand is highest. Decarbonisation must be achieved in a way that peak demand can always be met. achieved in a way that peak demand can always be met.

Heat Demand Variation Will be Challenging to Meet with Renewable Electricity Alone








Blogges

(street letter virke of karmine for the size of the properties of the size of the





the production of the control of the

How are Renewable Gases Produced?

Bio-Refining

Bio-Refining can be used to convert biomass into a number of useful products such as food, chemicals and renewable gases.

This is achieved through a number of different technologies including microbial fermentation, biocatalysis and thermochemical processes, to produce renewable gases such as bioLPG and rDME. Renewable gases such as rDME and bioLPG can also be used as hydrogen carriers due to the lower cost of transporting and storing these gases.

Power to Gas (P2G)

Power to gas involves using electrolysis to convert electricity to hydrogen. This can then be combined

with carbon to produce synthetic hydrocarbons with very low emissions if renewable electricity is used. These renewable fuels are much cheaper and easier to store than pure hydrogen due to their greater volumetric energy density.

Anaerobic Digestion (AD)

Anaerobic digestion is the breakdown of organic matter using micro-organisms in the absence of oxygen. This produces biogas which can be **upgraded to biomethane.** Biomethane can then be compressed into bioLNG which can be stored in tanks and used

in off-grid applications.

Gasification and Pyrolysis


Gasification and pyrolysis use heat, pressure and steam to convert biomass into renewable gases. Gasification is a

thermochemical process where materials decompose in an environment with less oxygen than is required for combustion. Pyrolysis is a similar process, performed at higher temperatures, but in the absence of oxygen.






Stratego (2018) Creating Hourly Profiles to Model both Demand and Supply
 ECOFYS (2018) Rural energy in Europe
 IEA (2020) Monthly generation of solar PV in Germany
 IEA (2020) Monthly generation of offshore wind in Germany



Factors That Make Consumers Unlikely To Upgrade Their Heating System


(Average % of Countries Surveyed)










Greenhouse Gas Emission Saving Relative to Oil^{11,12}








Significant Proportion of Households Cannot Afford Heat Pumps*





- R.IV European Environment Agency (2021) Air Quality in Europe 2021

 2. III NAEI (2020) Emission factors detailed by fuel and source

 3. Cedelft (2021) Emissions of (bio)LPG and other energy carriers in domestic heating, BBQs and forklift trucks

 4. SHV Energy (2022) Renewable DME

 4. JRC (2017) Solid and gaseous bioenergy pathways: input values and GHG emissions

 4. Bilans Ges (2022) Direct Emissions and Upstream Fuels

 5. European Commission (2018) Decentralised heat pumps: system benefits under different technical configurations

 6. Plancome deciles are 9 income figures that divide the population into 10 equal sized groups, the first decile represents the poorest 10% of the population.

 7. Eurostat (2022) Income Distribution by Quantiles

 7. Imperial College London (2020) The flexibility of gas: what is it worth?


 7. Entrog & Entsoe (2020) Scenario Results


 7. Energy (2016) Electricity, gas, heat integration via residential hybrid heating technologies

- ²³ Energy (2016) Electricity, gas, heat integration via residential hybrid heating technologies









BioLPG For Hard-to-Treat Rural Homes



Over a quarter (26%) of Germany's population live in rural areas; of these homes, 25% use heating oil.

Installing a bioLPG ready boiler, alongside thermal insulation would result in:



annual CO₂ savings of 63%, rising to **90%** 68% NOx savings and 66% PM when using bioLPG. emissions savings.

€933 annual energy bill savings and a capital cost back period of 8.4 years.25



BioLPG Supporting Net Zero Targets of a Cosmetic Industry



La Roche-Posay, offering innovative skincare solutions for fragile skin, became the first industrial site in France to use bioLPG in 2018.

This was a simple transition, as the product has no impact on the performance of their manufacturing activity and is easily incorporated into the distribution network of Primagaz France.

In 2005, the La-Roche-Posay site was producing $192tCO_2$ per year, which fell to zero in 2019 – with bioLPG being the last step towards carbon neutrality on the industrial site. ²⁶





 ^{24.3} EBA (2020) Biogas Success Stories 2020
 Liquid Gas Europe (2019) Beyond the Gas Grid: Residential and Industrial Case Studies



Policy Landscape

The EU has a target of a 55% reduction in greenhouse gas emissions by 2030 and a net zero ambition by 2050. It is critical that the legislative frameworks and associated policies enable a Just Energy Transition where no one is left behind. Solutions that are available, easily deployable, cost effective and socially acceptable will be needed to achieve ambitious climate targets, and in view of rising energy security concerns it is equally important to consider solutions that ensure supply security and energy system resilience. The role of off-grid renewable gases is critical in this respect as they can facilitate the sustainability journey of communities in rural areas that often do not have the luxury to choose from many sustainable alternatives that are cost effective as well as lower carbon.



Policy Recommendations




Recognise all Renewable Gas Production Pathways

All renewable gas production pathways and related technologies should be recognized in policy frameworks to support their development and uptake. This will help to diversify supply, ensure supply security and maximise production. Renewable gases can be produced through a host of technologies such as hydro-treatment of vegetable oils, fermentation, gasification, pyrolysis, anaerobic digestion, etc.



Support Renewable Ready Gas Boilers

Policies should support the use of gas boilers that can operate on renewable gases. Hybrid solutions must also be considered where gas boilers are combined with heat pumps or solar thermal units and can offer flexibility and resilience to the energy system on top of GHG emission reduction benefits. It is important that efficient renewable ready gas boilers are recognized as an energy efficiency measure in building regulations and energy performance certificates.



Develop Markets for Renewable Gases

Financial incentives in the form of tax rebates, capital grants and fuel subsidies should be deployed to encourage switching to all renewable technologies including renewable gases. Renewable gases that are produced off-site must be allowed to contribute to zero-emission buildings. Renewable gases use the existing infrastructure in achieving decarbonisation objectives and therefore can make the energy transition cost-efficient and affordable for end consumers. Intelligent policy design is needed to make sure that incentives for renewable liquid and gaseous fuels in one sector do not artificially raise their price in other sectors.



Facilitate Consumer Choice

There is no 'one size fits all' solution, certainly not for heat decarbonisation. Consumers should be made aware of possible options for decarbonising heat, including the benefits of using renewable gases in their current heating system. Policies should not pick favourites but instead should help guide consumer choices and help them decide what fits their needs while remaining aligned with our collective climate goals.



